



Scotchcal™ Graphic Film

with Comply™ Adhesive

IJ40C-10R and IJ40C-20R

For Solvent and UV Piezo Inkjet Printing Only

Product Description

Film IJ40C-10R (gloss) and IJ40C-20R (matte) are 3-mil vinyl films with a removable, pressure-sensitive adhesive and Comply adhesive for easier, bubble-free application. Available in a gloss or matte finish, it is designed for solvent and UV-based piezo inkjet printing where a good, versatile film is needed for general indoor and outdoor promotional graphics or for indoor floor graphics.

About Floor Graphics

Floor graphics are for use on indoor floors only. They require the use of 3M™ Scotchcal™ High Gloss Overlaminates 3648, which provides a slip-resistant surface.

Wall Graphics

Two mil cast films are typically the best choice for indoor smooth surface wall graphics, although four mil films may be suitable for shorter term applications. In either case, the user is responsible for determining the product's suitability, including adhesion and, if required, removal characteristics. Due to the wide variability of smooth indoor walls, neither finished graphics nor removal is warranted, even for removable or changeable films. Instruction Bulletin 5.37 provides comprehensive information for the most successful wall graphics film selection and application.

Characteristics

All values are typical for unprocessed film and are not for use in specifications. Contact your 3M representative for a custom specification.

Physical Characteristics

Characteristic	Value
Material	Vinyl
Color	White opaque
Gloss	Matte: IJ40C-20R Gloss: IJ40C-10R
Film thickness	Without adhesive: 3 mil (0.081 mm) With adhesive: 4.0 mil (0.102 mm)
Adhesive type	Pressure sensitive with air release channels
Adhesive color	Gray
Liner	Polycoated paper

Application Characteristics

Finished graphic application recommendations	Most Graphics Surface type: Smooth, flat and simple curved surfaces Substrate type: Metal, rigid plastic and painted substrates	Floor Graphics Only Surface type: Smooth, flat Substrate type: Most indoor floors including, tile, sealed concrete, Terrazzo, ceramic and finished wood
	Application temperature: <i>air and substrate</i> 40° to 100°F (4° to 38°C)	
Application method	Dry	
Finished graphic exposure temperature	-30° to +200°F (-34° to +93°C)	
Graphic removal	Removable, may require heat	

Warranty and Durability

3M Basic Product Warranty

This product has been tested and is believed to be a good product when used as recommended in this bulletin. The film is covered by the 3M Basic Product Warranty and is guaranteed to be free of physical and manufacturing defects. There is no warranty for printability, visual appearance, fitness for use or durability. See the 3M Graphics Market Center Warranty Brochure for the complete warranty and remedy details.

Expected Performance Life

Most Promotional Graphics: 5 years in a vertical exposure with typical usage may be expected

Indoor Floor Graphics: 3 months, when protected by 3M overlamine 3648, in a horizontal indoor exposure with typical usage may be expected.

Warranty and Limited Remedy

The following is made in lieu of all other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose or implied warranty arising out of a course of dealing, custom or usage of trade: all 3M products are warranted to be free of defects in materials and manufacture at the time of shipment and to meet the specifications stated in this Product Bulletin. 3M will replace or refund the price of any 3M materials that do not meet this warranty within the specified time periods. These remedies are exclusive. In no case shall 3M be liable for any direct, indirect, or consequential damages, including any labor or non 3M materials charges.

See the Graphics Market Center Warranty Brochure, which gives the terms, additional limitations of the warranty, if any, and limitations of liability.

Definitions

Vertical Exposure



face of graphic

The face of the graphic is $\pm 10^\circ$ from vertical.

Horizontal Exposure

face of graphic



The face of the graphic is $\pm 5^\circ$ from horizontal.

Fabrication

All Graphics

This film has been optimized to perform well with a variety of piezo inkjet printers and inks. It is the graphic manufacturer's responsibility to determine the film's suitability for use with their printers and inks.

To maximize the film performance:

- The typical maximum ink limit is 250%.
- Thoroughly dry the ink and film or properly cure the ink before storing or installing.
- Leave a small, unprinted margin (1/4 inch) on all edges. This helps to minimize edge curling when finished graphics will be sheeted and stacked for an extended period of time.

Always use the dry application method.

Additional Information for Floor Graphics

Applying an Overlamine, Cutting, Application and Removal

See Instruction Bulletin 5.19 for specific information on these tasks.

After applying overlamine 3648, soften any sharp corners by cutting radii on them. Use a hand cutter or cut with an electronic drum or flatbed plotter. This reduces the risk of corner lifting due to foot scuffing and equipment abrasion.

The film may be scrubbed, cleaned and waxed during routine maintenance of the floor.

Shelf Life, Storage and Shipping

Activity	Recommendations
Shelf life	Total shelf life: 2 years Up to 2 years unprocessed, <i>OR</i> Up to 1 year processed and applied within 1 year of processing
Storage conditions	<ul style="list-style-type: none"> • 90°F (32°C) maximum • Out of direct sunlight • Clean, dry area • Original container
Shipping finished graphics	Flat: may be separated by paper Roll: printed side out on 5 inch (13 cm) diameter or larger core

Health and Safety



When handling any chemical products, read the manufacturers' container labels and the Material Safety Data Sheets (MSDS) for important health, safety and environmental information. To obtain MSDS sheets for 3M products go to 3M.com/MSDS, or by mail or in case of an emergency, call 1-800-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturers' instructions for safe operation.

3M Related Literature

Before starting any job, be sure you have the most current Product and Instruction Bulletins.

The information in 3M Product and Instruction Bulletins is subject to change. Current Bulletins are available at 3Mgraphics.com. The following applicable Bulletins provide information and processes you need to properly make the graphics described in this Bulletin. Additional Bulletins may be needed as indicated in the 3M Related Literature section of other 3M components you use.

Subject	Type	Bulletin No.
Bulletin types: PB = Product Bulletin; PB-IB = Product & Instruction Bulletin; IB = Instruction Bulletin		
3M™ Scotchcal™ High Gloss Overlaminate 3648	PB	3648
Application, substrate selection, preparation and substrate-specific application techniques	IB	5.1
Application, general procedures for indoor and outdoor dry applications	IB	5.5
A Guide to Understanding and Applying Graphics to Common Indoor and Outdoor Wall Surfaces	IB	5.37
Floor Graphics: Make, Overlaminate, Apply, Maintain, Remove	IB	5.19
Storage, handling, maintenance, removal	IB	6.5
3M Graphics Center Warranty Brochure		

3M and Scotchcal are trademarks of 3M.



Commercial Graphics Division

3M Center, Building 220-12E-04
PO Box 33220
St. Paul, MN 55144-3220 USA
General Info. 1-800-374-6772
Technical Info. 1-800-328-3908
Fax 1-651-736-4233
www.3mgraphics.com