



## DATA SHEET DIGITAL PRINTING MATT PAPER

### P 150 NA

Matt 155 micron paper for solvent inkjet printers.

#### **SPECIFICATIONS:**

	<u>Average values</u>	<u>Standard</u>
• Thickness (µm):	155	NF X 41-026
• Specific weight (g/m <sup>2</sup> ):	150	
• Opacity (%):	> 85	

#### **PRINTER AND INK COMPATIBILITY:**

- Solvent inkjet printers.

#### **RECOMMENDATIONS:**

- Touch dry after less than 5 minutes depending on printer.
- The print may be cold laminated with a clear self-adhesive vinyl (Hexis V700) or hot laminated (hot encapsulation).
- The visual appearance of the print maybe modified/improved/protected by a judicious choice of a gloss, matt or satin lamination (V700).
- Before laminating or coating inks need to dry for 24 hours.
- Application temperature +15°C...+25°C (+59°F...+77°F) at 30...70% relative humidity.

#### **SHELF LIFE:**

- 1 year at +15°C...+25°C (+59°F...+77°F) and 50% relative humidity, rolls standing upright in a dustfree environment before usage and in the original packing.

#### **Note:**

If in doubt about the compatibility of the product with any particular application we recommend that the user carry out a trial before the final application or seek advice from the manufacturer. All data are believed to be correct but do not constitute a warranty, representation or promise, express or implied as to the condition, quality, merchantability, fitness for a product, or that such product will satisfy any requirement for a specific property or capacity or special methods, all such warranties being hereby expressly disclaimed. The buyer has to determine the suitability of the materials for the intended purpose prior to purchase. HEXIS S.A. or its affiliates assume no liability for claims beyond the replacement value of any product proven to be defective in material or workmanship and is in no way liable for direct, indirect, special, incidental damages or consequential loss including without limitation lost profits or loss of use, whether based on contract, tort or any other legal theory. Product specifications may change without prior notice. Our website is automatically updated: [www.hexisgroup.com](http://www.hexisgroup.com).